

# HIGH AFFINITY



**For Unsurpassed Durability and Long-Lasting Shine  
Will respond well to burnishing up to 1 time per week**



## Product Order # 16



### Product Specifications

% Solids	22
pH	8.5
Specific Gravity	1.024
Viscosity, cps	15
Color	White

Coverage per gallon, sq. ft.	1,500 – 2,500
Floor Types	All finishable floor types, including VCT, terrazzo, vinyl

The premium high solids durable floor finish designed to deliver an exceptional high depth of gloss.

- Durable high gloss finish that is designed to be extremely resistant to soil, scratching, scuffing and marking.
- Outstanding application among a broad range of environmental conditions and application techniques
- Formulated with special acrylic copolymer technology to withstand heavy traffic & maintain high shine
- Holds up & responds to both propane or electric burnishing
- Exceeds UL slip resistance classification.
- Compliant with California Air Resources Board VOC (Volatile Organic Compound) limit.
- Low odor for healthcare & 24/7 facilities.

### Recommended For

- Healthcare
- Government
- Commercial facilities
- Building service contractors
- Education

### Hazard Rating

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

Another similar P&G Pro Line finish to consider: **Dexterity** is a versatile finish for moderate burnishing up to 1 to 3 times per week.

SIZE	DESCRIPTION
4 - 1 gal./3.78L	Ready-to-use
1 - 5 gal./18.9L	Ready-to-use

# HIGH AFFINITY



**For Unsurpassed Durability and Long-Lasting Shine**  
**Will respond well to burnishing up to 1 time per week**

## DIRECTIONS FOR USE

### Initial Application:



1. Remove all old wax and floor finish with appropriate PGPL Floor Finish Stripper.



2. Rinse floor thoroughly with clear water and allow to dry.

3. Using a clean, dry rayon or microfiber flat mop, apply a uniform coat of finish. Allow to dry thoroughly (typically 30-40 minutes). Apply additional coats in the same manner and let dry. For very porous or highly worn floors, one initial coat of floor sealer is recommended.

### Day-to-Day Maintenance:



1. Sweep or dust mop as necessary.



2. Auto-scrubbing is recommended or damp mopping with PGPL Finish Floor Cleaner.



3. Will respond well to burnishing up to 1 time per week



4. Periodic deep scrub and recoat will be required to replenish the base film for best burnish results.

	YES	NO
Acrylic Copolymer Base	X	
Metal Interlock	X	
UHS Repairable	X	
UL Classified as to Slip Resistance	X	
Strips Easily	X	
DOT Regulated		X