





PRODUCT

	P&G PROLINE® HEAVY DUTY SPRAY CLEANER											
	DESCRIPTION											
	For automatic dilution. A powerful 2-in-1 heavy duty spray cleaner, designed for grease-cutting and vandalism/graffiti mark removal. Removes tough greasy soil from a variety of surfaces, and ink marks/graffiti from walls, countertops, and other surfaces. Also removes grease, grime, oils and lubricating compounds found in industrial settings. Non-butyl cleaner cleans as well as the leading competitive butyl cleaner.											
DISTRIBUTOR - CODE	FORMAT	CASE COUNT	UPC - CODE	DIMENSIONS								
	Jug	2 x 3,78 L	100-37000-57509-9 / case 0-37000-57509-2 / unit	<table><tr><td>weight</td><td>cube</td></tr><tr><td colspan="2">case = length x width x height</td></tr><tr><td>8,337 kg</td><td>20,954 dm³</td></tr><tr><td colspan="2">26,365 cm x 25,095 cm x 31,598 cm</td></tr></table>	weight	cube	case = length x width x height		8,337 kg	20,954 dm³	26,365 cm x 25,095 cm x 31,598 cm	
weight	cube											
case = length x width x height												
8,337 kg	20,954 dm³											
26,365 cm x 25,095 cm x 31,598 cm												
PRODUCT IMAGE		COMPONENTS		ACCESSORIES								
		<p>Butoxyethoxy ethanol Phenoxyethanol Monoethanolamine</p> <p>No phosphate Butyl free</p> <p>Biodegradable surfactants Environmentally friendly</p>		 Spray Bottle								

APPLICATIONS



Walls



Counter tops

NOT FOR USE ON :
Finished floor

NOTES

APPEARANCE

- Purple liquid

ODOUR

- Low chemical odour
- Clean, fresh scent

USAGE INSTRUCTIONS

MÉTHODE DE DILUTION

1 part concentrate to 8 parts water for use as spray cleaner :
approx. 3.78L of concentrate = approx. 34L of diluted product.

ATTACHING TO THE P&G DILUTION CENTER

1. Remove white shipping cap. DO NOT REMOVE BLACK PLUG FROM BOTTLE THROAT!
2. Screw on BLACK dispensing cap from dilution center product tube.
3. Push down while twisting.

MÉTHODE D'UTILISATION

1. fill properly labeled spray bottle from dilution center.
2. spray 15-20 cm/6-8 inches from hard, non-porous surfaces.
3. for tough soils and marks, let soak 3-5 mins.
4. wipe with paper towel or lintfree cloth.
5. use water rinse when needed.

Note: safe on most washable surfaces. however, on painted surfaces and wall covering test a small area before use. If applied to plastic or coated aluminum, wipe immediately and do not let soak.

