



## Great Burnish Response with Frequent Burnishing of 3 to 5 Times Per Week



### Product Order # 14



The floor finish designed to deliver a "wet look" gloss with frequent UHS (ultra high speed) burnishing habits.

- Great burnish response that "pops" with 2500+ rpm propane, battery or electric equipment
- Outstanding application among a broad range of environmental conditions and application techniques
- Excellent lay-down shine
- Resistant to dirt, scratching, scuffing and marking.
- Formulated with special acrylic copolymer technology to withstand heavy traffic & maintain high shine
- Exceeds UL slip resistance classification.
- Compliant with California Air Resources Board VOC (Volatile Organic Compound) limit.

### Product Specifications

% Solids	20
pH	8.5
Specific Gravity	1.024
Viscosity, cps	15
Color	White

Coverage per gallon, sq. ft.	1,500 – 2,500
Floor Types	All finishable floor types, including VCT, terrazzo, vinyl

### Recommended For

- Retail, Supermarket
- Healthcare
- Government
- Commercial facilities
- Building service contractors

### Hazard Rating

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

Another similar P&G Pro Line finish to consider: **Grand Opening** is a comparable UHS finish, designed for the ultimate in "wet look" gloss with daily burnishing.

SIZE	DESCRIPTION
1 – 5 gal./18.9L	Ready-to-use



## Great Burnish Response with Frequent Burnishing of 3 to 5 Times Per Week

### DIRECTIONS FOR USE

#### Initial Application:



1. Remove all old wax and floor finish with appropriate PGPL Floor Finish Stripper.



2. Rinse floor thoroughly with clear water and allow to dry.
3. Using a clean, dry rayon or microfiber flat mop, apply a uniform coat of finish. Allow to dry thoroughly (typically 30-40 minutes). Apply additional coats in the same manner and let dry. For very porous or highly worn floors, one initial coat of floor sealer is recommended.


#### Day-to-Day Maintenance:



1. Sweep or dust mop as necessary.



2. Auto-scrubbing is recommended or damp mopping with PGPL Finish Floor Cleaner.



3. For Frequent burnishing between 3 to 5 times per week to maintain gloss.



4. Periodic deep scrub and recoat will be required to replenish the base film for best burnish results.

	YES	NO
Acrylic Copolymer Base	X	
Metal Interlock	X	
UHS Repairable	X	
UL Classified as to Slip Resistance	X	
Strips Easily	X	
DOT Regulated		X