

DISINFECTING CLEANING WITH AN AUTO SCRUBBER

Tools Needed

- Wet Floor Sign
- Automatic Scrubber
- Measuring Cup
- Detail Mop

Product Needed


P&G Pro Line
Disinfectant
Floor Cleaner



FREQUENCY OF CLEANING: Daily or as needed depending on soil levels.

PREPARATION: Always dust mop area following the Dust Mop Procedure to remove grit and loose soil before performing this task. Collect all tools, equipment and products required. Ensure all equipment is operational. Review MSDS, product labels and caution statements. Choose appropriate safety equipment.

SPECIAL DIRECTIONS FOR THIS TASK: Start with clean pads or brushes. Empty solution and recovery tanks, clean and return equipment to storage area when finished. Remove wet floor sign only when surface is thoroughly dry.



STEP 1

- Remove grit and loose soil on finished floor surfaces following the Dust Mop Procedure. On non-finished or grouted floor surfaces use a broom or brush.

Note: Remove all loose objects on floor. Loose objects can become projectiles if struck by pads or brushes. Objects can damage floors if caught in pads or brushes.



STEP 2

- Put out wet floor sign in area to be serviced.



STEP 3

For General Cleaning

- Add ½ ounce floor cleaner per gallon warm water (1:256) to the automatic scrubber solution tank.

To Clean and Disinfect

- For water hardness up to 250 ppm, add 1 ounce (1:128) floor cleaner per gallon warm water.
- For water hardness over 250 ppm, add 1 1/3 ounces (1:96) floor cleaner per gallon warm water.



STEP 4

For General Cleaning

- Scrub area to be cleaned:
 - ☐ Pads or brushes down
 - ☐ Squeegee down
 - ☐ Solution control on
 - ☐ Vacuum on
- Overlap each pass until area is scrubbed completely.
- Absorb cleaning solution from corners, baseboards and squeegee trails with detail mop.



To Clean and Disinfect

- Scrub area to be cleaned:
 - ☐ Pads or brushes down
 - ☐ Squeegee up
 - ☐ Solution control on
 - ☐ Vacuum off
- Overlap each pass until area is scrubbed completely.
- To disinfect, cleaning solution should remain wet on the floor for 10 minutes.
- Pick up cleaning solution:
 - ☐ Pads or brushes down
 - ☐ Squeegee down
 - ☐ Solution control off
 - ☐ Vacuum on
- Absorb cleaning solution from corners, baseboards and squeegee trails with detail mop.

NOTE: Keep floor machine moving while pads/brushes are rotating to prevent damage to finish.