

# MOP-ON RESTORER

## Tools Needed

- Wet Floor Sign
- Mop Bucket and Wringer
- Clean, Dry Rayon Mop
- Plastic Liner

## Product Needed


P&G Pro Line  
Spray Buff / Maintainer



**FREQUENCY OF CLEANING:** Bi-weekly or as needed to repair surface imperfections which cannot be repaired with daily maintenance procedures.


**PREPARATION:** Collect all tools, equipment and products required. Ensure all equipment is operational. Review MSDS, product labels and caution statements. Choose appropriate safety equipment.

**SPECIAL DIRECTIONS FOR THIS TASK:** When finished, clean and return equipment to storage closet.



### STEP 1

- Remove grit and loose soil by following the Dust Mop Procedure.



### STEP 2


- Wet clean floor using one of the following procedures: Damp Mop Procedure, Disinfecting Damp Mop Procedure or Automatic Scrubber Floor Cleaning Procedure.



### STEP 3

- Put out wet floor sign in area to be serviced.


**NOTE: Floors must be completely dry before performing mop-on restore.**



### STEP 4

- Line mop bucket with plastic liner.
- Fill mop bucket to 3 gallon line with cold water.
- Add 1 bottle (1 gallon) spray buff / maintainer.


**NOTE: Proper dilution of spray buff / maintainer is 42 ounces to 1 gallon cold water. Amount of solution should be adjusted according to size of area to be serviced.**



### STEP 5

- Submerge mop in solution.

**NOTE: Always start with a clean, dry rayon mop.**



### STEP 6

- Twist lower half of mop in wringer and wring out solution.


**NOTE: Top portion of mop will feed mop with right amount of Spray Buff / Maintainer for a thin, uniform coat.**



### STEP 7


- Starting at farthest point from door, frame a 10 ft. by 10 ft. area with mop.
- Mop inside frame using a figure-8 motion.

**NOTE: Apply a thin, uniform coating.**




### STEP 8

- Move to next 10 ft. by 10 ft. area, working towards doorway and repeat Step 5 through Step 8.




### STEP 9

- When entire area is complete, remove liner from bucket, twist, tie and discard.



### STEP 10

- Product will dry to a dull haze.
- To restore gloss by Burnishing follow the Burnishing Procedure.
- To restore gloss by buffing proceed to Step 11.



### STEP 11

- Mount red buffing floor pad to machine.
- Starting at farthest point from door, buff area using a left to right / right to left motion, overlapping each pass.

**NOTE: Keep floor machine moving while buffing. Running machine in same spot can leave deep swirls in the finish.**



**NOTE: Flip or change pads as needed.**