



For Great Durability and Long-Lasting Shine
For low frequency burnishing up to 1 time per week



Product Order
13



The floor finish product designed to deliver great shine & durability with low maintenance.

- Unsurpassed application robustness in a wide-range of environmental conditions
- Excellent initial shine
- Holds up & responds to both propane and electric burnishing
- Outstanding application among a broad range of environmental conditions and application techniques
- Formulated with special acrylic copolymer technology to withstand heavy traffic & maintain high shine
- Exceeds UL slip resistance classification.
- Compliant with California Air Resources Board VOC (Volatile Organic Compound) limit.

Product Specifications

% Solids	19
pH	8.5
Specific Gravity	1.024
Viscosity, cps	15
Color	White

Coverage per gallon, sq. ft.	1,500 – 2,500
Floor Types	All finishable floor types, including VCT, terrazzo, vinyl

Recommended For

- Education
- Building service contractors
- Commercial buildings
- Government

Hazard Rating

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

Another similar P&G Pro Line finish to consider: **Principal**, for basic protection and for infrequent burnishing less than 2 times per month

SIZE	DESCRIPTION
4 - 1 gal./3.78L	Ready-to-use
1 - 5 gal./18.9L	Ready-to-use



**For Great Durability and Long-Lasting Shine
For low frequency burnishing up to 1 time per week**



DIRECTIONS FOR USE

Initial Application:



1. Remove all old wax and floor finish with appropriate PGPL Floor Finish Stripper.



2. Rinse floor thoroughly with clear water and allow to dry.

3. Using a clean, dry rayon or microfiber flat mop, apply a uniform coat of finish. Allow to dry thoroughly (typically 30-40 minutes). Apply additional coats in the same manner and let dry. For very porous or highly worn floors, one initial coat of floor sealer is recommended.

Day-to-Day Maintenance:



1. Sweep or dust mop as necessary.



2. Auto-scrubbing is recommended or damp mopping with PGPL Finish Floor Cleaner.



3. For low frequency burnishing up to 1 time per week



4. Periodic deep scrub and recoat will be required to replenish the base film for best burnish results.

	YES	NO
Acrylic Copolymer Base	X	
Metal Interlock	X	
UHS Repairable	X	
UL Classified as to Slip Resistance	X	
Strips Easily	X	
DOT Regulated		X