SPRAY BUFF

Tools Needed

- · Wet Floor Sign
- Trigger Sprayer & Bottle
- 175+ RPM Floor Machine
- Floor Pads
- Dust Mop



Product Needed

P&G Pro Line Spray Buff / Maintainer



FREQUENCY OF CLEANING: Bi-weekly or as needed to repair surface imperfections that cannot be repaired with daily maintenance procedures.

PREPARATION: Collect all tools, equipment and products required. Ensure all equipment is operational. Review MSDS, product labels and caution statements. Choose appropriate safety equipment.

SPECIAL DIRECTIONS FOR THIS TASK: Floor must be completely dry before performing this procedure. When finished, clean and return equipment to storage area. Remove wet floor sign only when surface is thoroughly dry.



STEP 1

 Remove grit and loose soil by following the <u>Dust Mop Procedure</u>.



STEP 2

 Wet clean floor using one of the following procedures: <u>Damp Mop Procedure</u>, <u>Disinfecting Damp Mop Procedure</u> or <u>Automatic Scrubber Floor Cleaning</u> <u>Procedure</u>.



STEP 3

Put out wet floor sign in area to be mopped.

NOTE: Floors must be completely dry before spray buffing.



STEP 4

 Pour Spray Buff / Maintainer into spray bottle.



STEP 5

- Mount red floor pad to machine.
- Lightly spray product on pad to pre-moisten.



STEP (

 Starting at farthest point from door, spray solution lightly (2 – 3 full sprays) ahead of pad.



overlapping each pass.

Spread product in 3 ft. by 3 ft. area with

buffer using a left to right / right to left motion,

- Return and machine buff to deep gloss.
- Move to next 3 ft. by 3 ft. area, working towards doorway and repeat Step 6.

NOTE: Keep floor machine moving while buffing. Running machine in same spot can leave deep swirls in the finish.

NOTE: Flip or change pads as needed. When flipping or changing pads, lightly spray pad with Spray Buff / Maintainer to pre-moisten.



STEP 7

 Dust mop area to remove loose residue left by pad following the <u>Dust Mop Procedure</u>.